

AC /DC Electronic Load 300Watt



OVERVIEW

- CC / CR and Crest Factor Mode
- Display 4 1/2 digits for V / C / W / VA
- Configurable in main frame 3300
- Last setting memory GO / NG limit check
- Protection against V / A / W / °C

TYPES

Type	Power W	Current A _{rms}	Voltage V _{rms}	CC Mode 10 – 400Hz	CR Mode DC – 400 Hz	Monitor A / V
3250	300	20	60	0 – 10 / 20 A _{rms}	0,3 – 1,2 – 4,8 kΩ	2
3251	300	8	150	0 – 4 / 8 A _{rms}	1,875 – 7,5 – 30 kΩ	0,8
3252	300	4	300	0 – 2 / 4 A _{rms}	7,5 – 30 – 120 kΩ	0,4

TECHNICAL DATAS

Mainframe	3300 (Manual and Remote) 3301 (Manual only) 3302 (Manual and Remote)
Cooling	Force air (see mainframe)
Resolution CC Mode	3250 2.5 / 5 mA 3251 1 / 2 mA 3252 0.5 / 1 mA
Resolution CR Mode	3250 0.21 / 0.83 mS* 3251 0.033 / 0.13 mS* 3252 0.0083 / 0.033 mS*
Resolution DVM	3250 0 – 60 V / 0.01 V 3251 0 – 150 V / 0.01 V 3252 0 – 300 V / 0.01 V
Watt meter	0.0 – 300 W / 0.1 W
Weight	3.5 kg
Dimensions	108 x 143 x 405 mm (W x H x D)

*mS=milli-Siemens= 1 kΩ